

CLIPPER
MOTOR YACHTS

Clipper 34 Sedan



CLIPPER
MOTOR YACHTS

W

W~YACHT

W-Yacht * Tel +47 98218209 * post@w-yacht.no * www.clipper.no

STANDARD SPECIFICATIONS

CLIPPER 34 SEDAN

General Specifications

LOA: 37'2" (11,33 meters)
Beam: 11'10" (3,68 meters)
Draft: 2'8" (0,82 meters)
Displacement: 9,5 ton (20 948 LBS)
Standard engine: 1 x Cummins QSB 230HP
Fuel capacity: 300 gallon (1 136 liter)
Water capacity: 150 gallon (568 liter)
Holding tank capacity: 30 gallon (114 liter)

General Construction

Fibreglass bow platform.
Fibreglass swim platform.
Non-skid fibreglass deck.
International paints micron CSC anti-fouling.
Hull- and superstructure in hand laid-up moulded fibreglass.
Vinylester resin in the outer layers of the hull.
Solid fibreglass hull with vinylester resin in the outer layers.
Solid keel with foam filled or hollow fibreglass stringers for re-enforcement.
Deck and superstructure is a single mould with structural coring as required (NIDA).

Flybridge

Helm seat.
Stainless steel steering wheel.
Engine gauges.
Morse engine controls.
Hinged radar arch.
Two (2) radar arch lights.
One (1) DC outlet.
One (1) double AC outlet.
Anchor light.
Navigation lights.
Stainless steel flag base.
Electric horn.
Storage cabinet in front of helm seat.
Two (2) storage lockers/seats.

Cockpit and Main Deck

One (1) double AC outlet.
Hatch to access lazarette.
Stainless steel- and teak ladder leading to fly bridge.
Transom door leading to swim platform.
Door to access saloon from aft deck.
Stainless steel anchor roller.
45 LBS C.Q.R. anchor.

Other Exterior Fittings and Equipment

Stainless steel railing- and stanchions around all edges.
Fibreglass non-skid deck on all deck surfaces.
Six (6) stainless steel mooring cleats (three on each side deck).
Stainless steel fuel-, water- and waste tank deck fittings on both side decks.
Stainless steel portholes.
Tempered glass windows.

Saloon, Dinette and Galley

Six (6) ceiling lights.
Double AC outlets.
“H” shaped dinette teak table with hi-low function. Dinette to be converted to a double bed.
Storage room under dinette seats.
Two (2) drawers under one of the dinette seats.
Settee on starboard side with drawers under. Settee also to be converted into a double bed.
5" thick fabric covered foam cushions on dinette seats.
Corian countertop in galley.
Tundra TJ42 130 litre refrigerator with ice box.
Seaward #3172.1001 gas stove with three burners and oven.
Double stainless steel sink in galley.
Sink faucet with pullout spout (single lever).
Four (3) drawers in galley.
Three (3) cabinets in galley.
Hatch on galley countertop for garbage.
Teak railing on the saloon ceiling.

Helm Station

Raised helm dash.
One (1) DC outlet.
Door to access helm station from starboard side deck.
AC- and DC electrical panels.
Built in helm seat.
Morse engine control levers.
Horn control.
Teak- and stainless steel steering wheel.

Two (2) windshield wipers.

Master Stateroom

Two (2) ceiling lights.
Two (2) double AC outlets.
Large island bed.
5" thick fabric covered foam mattress.
Two (2) golden Perko reading lights.
Four (4) drawers under the bed.
Two (2) hanging lockers.
Two (2) opening, screened porthole window.
One (1) opening, screened overhead hatch.

Head / Shower

One (1) ceiling light.
One (1) double AC outlet.
TMC manual toilet.
Vanity mirror.
Stainless steel sink and extractable shower-/sink faucet.
Teak grating.
One (1) opening, screened porthole window.

Other Interior Fittings and Equipment

Hand made teak flooring throughout.
Teak panelling- and cabinetry throughout.
Curtains on all windows.
Screens on all sliding windows.
Soft vinyl headliners.

Engine Room, Propulsion and Fresh Water System

Cummins engine QSB 230 HP with 160 amp alternator.
Seafire FD350MA automatic fire extinguisher.
Engine room sound insulation.
Aluminium plate floors.
Four (3) engine room ceiling lights.
Engine room blower.
Fibreglass fuel tanks (2 x 150 gallon / 2 x 568 liter).
2" stainless steel shaft.
PYI dripless shaft seal.
Precision 4 blade propeller.
Hynautic dual stations hydraulic steering.
Morse dual stations engine lever cable controls.
Exhaust muffler.

Sea cock and strainer on engine raw water intake.
Racor single fuel filter.
Three (3) automatic bilge pumps.
One (1) manual bilge pump.
Holding tank with macerator pump.
Fibreglass water tanks (2 x 75 gallon / 2 x 284 liter)
Fresh water pump.
Two (2) fresh water intakes.
Water heater.

Electrical

Battery charger.
Three (3) 12V/200AMP batteries.
Fibreglass boxes with hatches for batteries.
Master control panel (AC/DC circuit breakers).
Bonded electrical system.
Color coded electrical system.
110V/220V AC outlets.
12V lighting throughout interior and exterior.
Shore power connector on starboard side forward of the helm station.

Other Equipment

Emergency tiller
Zincs



W~YACHT

E-mail: post@w-yacht.no
Web: www.clipper.no
Tel: +47 98218209
Fax: +47 52774058

CLIPPER
MOTOR YACHTS